

## DECLARATION OF CONFORMITY Nr. 2023-02

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa.

Hot-dip galvanizing with a minimum of 50 µm.

### U-type

**73501** Post foot U-type 50x40  
**73502** Post foot U-type 50x60  
**73503** Post foot U-type 75x40  
**73504** Post foot U-type 75x60  
**73506** Post foot U-type 90x90  
**73507** Post foot U-type 100x40  
**73508** Post foot U-type 100x60  
**73509** Post foot U-type 100x90  
**73511** Post foot U-type 120x70  
**73512** Post foot U-type 120x90  
**73513** Post foot U-type 125x90  
**73514** Post foot U-type 150x60  
**73520** Post foot U-type 140x90  
**73525** Post foot U-type 45x40  
**73527** Post foot U-type 48x40  
**73535** Post foot U-type 80x60  
**73551** Post foot U-type 90x90  
**73552** Post foot U-type 100x70

### U-type STRONG

**73531** Post foot U-type 50x40  
**73532** Post foot U-type 100x60

### L-type

**73515** Post foot L-type 70x60  
**73524** Post foot L-type 84x90

### I-type

**73516** Post foot I-type 90x60

### Adjustable

**73517** Post foot, adjust. 70-120  
**73522** Post foot, adjust. 80-160  
**73519** Post foot adjust. 90-150, adjust. leg 240-290  
**73523** Post foot adjust. 70-105, adjust. leg 240-290  
**73518** Post foot adjust. 105-160 with sole (leg 115-185)  
**73521** Post foot adjust. 80-120 with sole (leg 115-165)  
**73553** Post foot adjust. 80-100 with sole (leg 115-165)  
**73554** Post foot adjust. 80-110 with sole (leg 115-165)

### With ground plate

**73801** Post foot 50x50 l=150 with ground plate, type B  
**73802** Post foot 50x100 l=150 with ground plate, type B  
**73803** Post foot 75x75 l=150 with ground plate, type B  
**73804** Post foot 90x90 l=150 with ground plate, type B  
**73805** Post foot 100x100 l=150 with ground plate, type B  
**73806** Post foot 120x120 l=150 with ground plate, type B  
**73807** Post foot 140x140 l=200 with ground plate, type B

### Screwpost

**73933** Screwpost 50x70x125 screw-in, L=800, d=50  
**73934** Screwpost 90x70x125 screw-in, L=1000, d=70  
**73935** Screwpost 100x70x125 screw-in, L=1000, d=70  
**73936** Screwpost 100x70x125 screw-in, L=1200, d=70  
**73937** Screwpost 100x100 screw-in, L=1200, d=92  
**73938** Screwpost 100x100 screw-in, L=1400, d=92

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa.

Zinc coating thickness: 5-8 µm.

**Threaded column shoe**

**74001** Threaded column shoe 50x50x5,0 M10x150

**74002** Threaded column shoe 60x60x4,0 M16x120

**74003** Threaded column shoe 100x70x8,0 M20x150

**74004** Threaded column shoe 100x100x8,0 M30x200

**74007** Threaded column shoe 100x100x8,0 M24x200

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa.

Hot-dip galvanizing with a minimum of 50 µm.

**73901** Drive-in post support 50x50mm, L=600mm, type A

**73902** Drive-in post support 50x100mm L=750mm, type A

**73903** Drive-in post support 75x75mm, L=750mm, type A

**73904** Drive-in post support 100x100mm, L=750mm, type A

**73905** Drive-in post support 90x90mm, L=750mm, type A

**73906** Drive-in post support 95x95mm, L=750mm, type A

**73911** Circular drive-in post support 80mm, L=750mm, type A

**73912** Circular drive-in post support 100mm, L=750, type A

**73915** Screw-in post support 50x50, L=650mm

**73916** Screw-in post support 100x100, L=750mm

**73931** Post foot 70-105 adjust. /screw-in L=750mm

Signed on behalf of the distributor by:



**Lauri Kivi**

CEO

Member of the Board



**Kristi Voorel**

Quality Manager