

## DECLARATION OF CONFORMITY Nr. 2023-04

The listed spacers are used to create a protective layer in concrete structures. Spacers are used on soft base for the installation of reinforcement up to 20mm. Installation frequency of use 4pcs/m<sup>2</sup>. Installation at the crossing points of the reinforcement allows two reinforcement grids to be interconnected.

Diameter: 43 mm

Base: 88 mm

Product	Max load	Material
SEEN15/20 Spacer "mushroom" 15/20 (200pcs)	215 kg	100% recycled plastic PP*
SEEN25/30 Spacer "mushroom" 25/30 (200pcs)	210 kg	100% recycled plastic PP
SEEN35/40 Spacer " mushroom" 35/40 (200pcs)	190 kg	100% recycled plastic PP
SEEN45/50 Spacer "mushroom" 45/50 (200pcs)	185 kg	100% recycled plastic PP
SEEN55/60 Spacer "mushroom" 55/60 (150pcs)	160 kg	HDPE**
SEEN65/70 Spacer "mushroom" 65/70 (200pcs)	160 kg	HDPE
SEEN75/80 Spacer "mushroom" 75/80 (200pcs)	160 kg	HDPE
SEEN90/100 Spacer "mushroom" 90/100 "(200pcs)	140 kg	HDPE
82320 Spacer "mushroom" 15/20 (50pcs)	215 kg	100% recycled plastic PP
82330 Spacer "mushroom" 25/30 (50pcs)	210 kg	100% recycled plastic PP
82340 Spacer " mushroom" 35/40 (50pcs)	190 kg	100% recycled plastic PP
82350 Spacer "mushroom" 45/50 (50pcs)	185 kg	100% recycled plastic PP

\* Polypropylene or polypropylene

\*\* High-density polyethylene

Signed on behalf of the manufacturer by:



**Lauri Kivi**  
 CEO  
 Member of the Board



**Kristi Voorel**  
 Quality Manager